

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**






## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>G01P 15/08, 15/04, 7/00, A63F 9/22, G06F 3/00</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 97/46888</b> <b>(43) International Publication Date:</b> 11 December 1997 (11.12.97)
<b>(21) International Application Number:</b> PCT/JP97/01730 <b>(22) International Filing Date:</b> 23 May 1997 (23.05.97)  <b>(30) Priority Data:</b> 8/143028                      5 June 1996 (05.06.96)                      JP  <b>(71) Applicant (for all designated States except US):</b> CASIO COMPUTER CO., LTD. [JP/JP]; 6-1, Nishi-Shinjuku 2-chome, Shinjuku-ku, Tokyo 160 (JP).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> TONOMURA, Keisuke [JP/JP]; 1-22-37-103, Musashinodai, Fussa-shi, Tokyo 197 (JP). YAMAGISHI, Masakatsu [JP/JP]; 1202, Fussa, Fussa-shi, Tokyo 197 (JP).  <b>(74) Agents:</b> SUZUYE, Takehiko et al.; Suzuye & Suzuye, 7-2, Kasumigaseki 3-chome, Chiyoda-ku, Tokyo 100 (JP).		<b>(81) Designated States:</b> CN, KR, SG, US, European patent (DE, FR, GB, IT).  <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>

**(54) Title:** MOVEMENT MEASURING DEVICE, ELECTRONIC GAME MACHINE INCLUDING MOVEMENT MEASURING DEVICE, AND METHOD OF PLAYING GAME MACHINE

**(57) Abstract**

A movement measuring device determines the speed of the body's specific movement on the basis of the maximum value of the acceleration sensed by an acceleration sensing unit attached to the body, when the body has made a specific movement. For example, when the player wears the device on his arm and makes a punching motion, the punching speed is found from the maximum acceleration resulting from the punching action. Furthermore, a game device obtains data indicating the magnitude of a specific movement of the body, on the basis of the acceleration sensed by an acceleration sensing unit, and then decides the outcome of the game is decided on the basis of the strength and weakness of the punch. This enables the user to easily play a fighting sport game involving the player's actual punching motions anywhere.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

## D E S C R I P T I O N

5                   MOVEMENT MEASURING DEVICE, ELECTRONIC GAME  
MACHINE INCLUDING MOVEMENT MEASURING DEVICE,  
AND METHOD OF PLAYING GAME MACHINE

## Technical Field

                  This invention relates to a movement measuring  
device for easily measuring the momentum caused by the  
10                  movement of the human body, an electronic game machine  
including the movement measuring device, and a method  
of playing the game machine.

## Background Art

                  A large variety of electronic game machines have  
15                  come in practice. Recently, fighting sport game  
products have appeared on the market.

                  For instance, in a computer video game using a  
display screen, a human character appearing on the  
screen is moved by the key operation of the controller  
20                  to represent various actions, including punching and  
kicking, so that the character may fight with another  
human character manipulated by the computer-side or  
the opponent's controller. In this case, the player  
forcing the human character to make a fight has only to  
25                  operate the controller's keys, so there is a big gap  
between the computer video game and actual combative  
sports, which dampens the pleasure of playing the game.

                  There has been a game machine, with which a player  
competes with the opponent for destructive power. Such

a game machine senses the impact force exerted on the target that the player punches, for example. In this case, an object to be punched, serving as the target, is needed. Moreover, to sense the impact force exerted on the target, a large, complicated sensing device is required. For these reasons, game machines of this type have the problem of being suitable only for use in amusement arcades.

Accordingly, there has been no means for easily sensing the impact force corresponding to the movement of the body with a compact structure and it has been impossible to construct a game machine that enables the player to easily play a fighting sport game involving actual fighting actions anywhere.

#### Disclosure of Invention

A first object of the present invention is to provide a movement measuring device capable of easily sensing the speed and impact force of the action of an actual human body with a compact structure without requiring an object serving as a target.

A second object of the present invention is to provide an electronic game machine including a movement measuring device which enables the player to play a fighting sport game involving actual fighting actions of the player anywhere.

A movement measuring device of the present invention comprises: an acceleration sensing section

that is worn on the body and senses the acceleration of the body's movement; a maximum acceleration sensing section for sensing the maximum value of the acceleration sensed by the acceleration sensing section in the course of a specific movement of the body; and a speed computing section for determining the speed produced by the specific movement of the body on the basis of the maximum value of the acceleration sensed by the maximum acceleration sensing section. For example, when a player with the moving measuring device on his arm punches, the acceleration produced by the punching action is sensed by the acceleration sensing means and the maximum acceleration is sensed by the maximum acceleration sensing section. The speed computing section determines the punching speed from the maximum acceleration. Setting weight enables the impact force to be obtained from the weight and the punching speed. Therefore, the player's actual punching speed and impact force can be measured with the compact device having the simple configuration.

A game machine of the present invention comprises: an acceleration sensing section that is worn on the body and senses the acceleration of the body's movement; a computing section for obtaining data indicating the magnitude of movement on the basis of the acceleration sensed by the acceleration sensing section; and decision means for determining victory or defeat on the

basis of the data indicating the magnitude of a specific movement of the body obtained by the computing section. For example, when a player with the game machine on his arm punches, victory or defeat is  
5 determined by the strength and weakness of the punch. This enables the player to easily play a fighting sport game involving actual fighting actions anywhere.

#### Brief Description of the Drawings

FIG. 1A is a front view of a wristwatch device  
10 according to a first embodiment of an electronic game machine including a movement measuring device of the present invention;

FIG. 1B illustrates an acceleration sensor;

FIG. 2 shows how the acceleration sensor senses  
15 the acceleration caused by the movement of a person wearing the wristwatch device of FIG. 1;

FIG. 3 is a block diagram of the electronic circuit of the wristwatch device in FIG. 1;

FIG. 4 shows the structure of the individual  
20 registers for power measurement mode and game mode provided in the RAM of the electronic circuit of FIG. 3;

FIG. 5 is a K value setting table according to world ranking which is referred to when offensive  
25 strength A is determined in the game mode;

FIG. 6 is a defense capacity setting table referred to when defense capacity D is determined in



the game mode;

FIGS. 7A and 7B are ranking update tables referred to when the number of places up or down in world ranking according to the victory or defeat pattern in the game mode is determined--FIG. 7A is a number-of-ranks-up setting table according to the victory pattern and FIG. 7B is a number-of-ranks-down setting table according to the defeat pattern;

FIG. 8 is views of the initial screens corresponding to the individual operation modes;

FIG. 9 is a flowchart of the measurement mode process in the power measurement mode of the wristwatch device of FIG. 1;

FIG. 10 is a flowchart of the measurement process in the measurement mode process in the power measurement mode;

FIG. 11 illustrates display operations in the measurement mode process in the power measurement mode;

FIG. 12 is a timing chart for changes in the sound and representation in the measurement process in the power measurement mode;

FIG. 13 is a flowchart for the game mode process in the punching game mode;

FIG. 14 is a flowchart of the battle process in the game mode process in the punching game mode of the wristwatch device;

process in the punching game mode;

FIG. 16 is a timing chart to help explain the elapsed time in the game mode process in the punching game mode;

5           FIG. 17 is a block diagram of the circuit of an electronic wristwatch according to a second embodiment of the present invention; and

FIG. 18 is a flowchart for a game process.

#### Best Mode of Carrying Out the Invention

10           (1) First Embodiment

A first embodiment of the present invention will be explained by reference to FIGS. 1 to 16.

15           FIG. 1A is a front view of a wristwatch device according to a first embodiment of an electronic game machine including a movement measuring device of the present invention. FIG. 1B illustrates an acceleration sensor.

20           A watch body 11 is as large as the ordinary wristwatch and can be worn around the wrist or the ankle with a wristband 11a. Inside the watch body 11, there are provided an acceleration sensor 12 and an electronic circuit that supervises various watch functions.

25           The acceleration sensor 12 is such that, for example, a two-ply rectangular plate-like piezoelectric element 12b is housed in a cylindrical case 12a, both sides of the bottom of the piezoelectric element 12b

being connected to two lead wires 12c, as shown in FIG. 1B. The sensor senses acceleration by receiving the voltage generated as a result of the bending of the piezoelectric element 12b in vibration.

5           The acceleration sensor 12 is placed so as to correspond to the nine o'clock position on the watch body 11. The sensor is set in the direction in which a positive voltage is sensed in proportion to the acceleration at which the watch body 11 moves in the  
10           direction of nine o'clock and in which a negative voltage is sensed in proportion to the acceleration at which the watch body moves in the direction of three o'clock.

          FIG. 2 shows how the acceleration sensor senses  
15           the acceleration caused by the movement of a player wearing the wristwatch device.

          For example, the player puts the wristwatch body 11 on his right arm, his dominant arm. When he punches as shown by (A) to (E) in FIG. 2, the voltage generated  
20           by the acceleration sensor 12 is as follows: in the striking period corresponding to (A) to (C), a positive voltage proportional to an increase in the speed in the direction of striking is sensed, and at the turning point where the punching arm has stretched out com-  
-           pletely, the maximum negative peak voltage is sensed.  
25

          Since the maximum speed of the punch in the punching action is almost linearly proportional to the

acceleration peak value B sensed by the acceleration sensor 12, the maximum speed of the punch is determined by multiplying the acceleration peak value B by a constant taking into account the inclination of the proportional straight line.

FIG. 3 is a block diagram of the electronic circuit of the wristwatch device.

The electronic circuit of the wristwatch device is provided with a CPU 13.

According to each of the acceleration data inputted from the acceleration sensor 12 via an A/D conversion circuit 14, the key operation signal inputted from a key section 15, and the time and date count data inputted from an oscillation circuit 16 via a frequency dividing circuit 17 and a time and date counting circuit 18, the CPU 13 starts the system program previously stored in a ROM 19 and controls the operation of each circuit according to the system program. Connected to the CPU 13 are not only the A/D conversion circuit 14, key section 15, time and date counting circuit 18, and ROM 19 but also a RAM 20, an alarm section 21, and a display section 22.

The A/D conversion circuit 14 converts the voltage signal corresponding to the sensed acceleration outputted from the acceleration sensor 12 into digital data and sends the digital data to the CPU 13. In this case, the A/D conversion circuit 14 converts the

voltage signal corresponding to an acceleration of -60G to +60G sensed by the acceleration sensor 12 into the digital data ranging from -128 to +128 and sends the digital data to the CPU 13.

5           The key section 15 is provided with S1 key, S2 key, S3 key, FO key, and SM key that are operated when various functions are executed in the various modes, including the basic watch mode, power measurement mode, and game mode in the wristwatch device.

10           Specifically, in the basic watch mode, for example, the present date and time data items corresponding to the time and date counting data inputted from the time and date counting circuit 18 appear on the display section 22. In the power measurement mode, for example,

15           on the basis of the acceleration data sensed by the acceleration sensor 12 as a result of the punching action of the player, the punch speed and the destructive power of the punch (impact force) are measured and displayed. In the game mode, for example, on the basis

20           of the acceleration data sensed by the acceleration sensor 12 as a result of the punching action of the player, the offensive strength and defense capacity against the imaginary opponent is determined and victory or defeat is judged. Then, the judgment result

25           is displayed.

          The ROM 19 stores not only the system program that supervises the overall control of the electronic

circuit but also a subprogram that supervises control corresponding to the various operation modes, including the basic watch mode, power measurement mode, and game mode, and the preset table data items.

5           FIG. 4 shows the structure of the individual registers for the power measuring mode and game mode provided in the RAM 20 of the electronic circuit in the wristwatch device.

          The measurement-mode registers in the RAM 20  
10       include, for example, a first measurement register 20a, a second measurement register 20b, and a third measurement register 20c that store the punching speed and the destructive power (impact force) of the punch measured on the basis of the acceleration data sensed by the  
15       acceleration sensor 12 as a result of the punching action of the player, as a first measured value, a second measured value, and a third measured value, respectively. The measurement-mode registers further include a maximum value register 20d that stores the  
20       maximum punching speed and maximum punch destructive power among the values of power measured until that time and a weight register 20e and a dominant arm register 20f in which the player's weight and the dominant arm wearing the wristwatch device are set  
25       respectively.

          The punching speed  $V$  in the punching action of the player is determined using equation 1. The punch

destructive power (impact force) P is found using equation 2.

Specifically, if the maximum value of the acceleration data items obtained from the acceleration sensor 12 via the A/D conversion circuit 14 is C and the player's weight is W, the punching speed V will be:

$$V = 0.8 \times |C| \quad (\text{the figures in one decimal place or below are rounded off}) \quad \dots [1]$$

For example, if the acceleration data obtained from the A/D conversion circuit 14 as a result of the punching action of the player indicates "54" (an acceleration of about 25G), the punching speed V will be:

$$\begin{aligned} V &= 0.8 \times 54 = 43.2 \\ &= 43 \end{aligned}$$

The punch destructive power (impact force) P will be:

$$P = 0.003 \times W \times V^2 \quad (\text{the figures in one decimal place or below are rounded off}) \quad \dots [2]$$

For example, in the case where the punching speed V obtained on the basis of an acceleration data item of "54" (an acceleration of about 25G) as a result of the punching action of the player is "43" and the player's weight W is 35 Kg, the punch destructive power (impact force) P will be:

$$\begin{aligned} P &= 0.003 \times 35 \times 43 \times 43 = 194.145 \\ &= 194 \end{aligned}$$

The game-mode registers in the RAM 20 include a player's own stamina register 20g into which the result of subtracting a value corresponding to the defense capacity D (damage) in the present round from a stamina of, for example, 50 points given to the player at the start of the game is stored, an opponent's stamina register 20h into which the result of subtracting a value corresponding to the offensive strength A in the present round from a stamina of 50 points given to the imaginary opponent at the start of the game is stored, a world rank register 20i into which the player's world rank, going up and down in the 30 world ranks depending on the victory or defeat pattern determined by the player's own stamina and the opponent's stamina at the end of the round, is stored, a number-of-wins-and-defeats register 20j into which the number of wins and defeats up to now is stored, and a number-of-KO-wins-and-defeats register 20k into which the number of KO wins and defeats up to now is stored.

The offensive strength A that causes the opponent to consume his stamina is determined using equation 3.

Specifically, if the punch destructive power is P, the punching speed is V, and the world ranking coefficient is R, the offensive strength A will be:

$A = P \times R$  (the figures in one decimal place or below are rounded off)

$$= K \times V^2 \quad \dots [3]$$



K is a coefficient taking into account a specific weight preset according to the player's world rank. Namely, the offensive strength A is found using the punching speed V obtained from equation 1 as a result of the punching action of the player and the coefficient K corresponding to the player's world rank at present.

FIG. 5 is a K value setting table according to world ranking which is referred to when offensive strength A is determined in the game mode of the wristwatch device.

The K value setting table according to world ranking is stored in advance in the ROM 19, for example.

For example, if the acceleration data obtained from the A/D conversion circuit 14 as a result of the punching action of the player indicates "54" (an acceleration of about 25G) and the player's world rank at present is the twelfth rank, offensive strength A will be:

$$\begin{aligned} V &= 0.8 \times 54 = 43.2 = 43 \\ A &= 0.007 \times 43 \times 43 = 12.943 \\ &= 12 \end{aligned}$$

The defense capacity D (damage) that suppresses the consumption of the player's stamina caused by the attack of the imaginary opponent is determined according to the player's world rank at present and the defensive punching speed V.

FIG. 6 is a defense capacity setting table referred to when defense capacity D is determined in the game mode of the wristwatch device.

The defense capacity setting table is stored in advance in the ROM 19, for example.

In this case, if the defensive punching speed V does not increase as the player's world rank at present gets higher, the defense capacity D will decrease and a value subtracted from the player's own stamina will become larger.

For example, if the acceleration data obtained from the A/D conversion circuit 14 as a result of the defensive punching action of the player indicates "21" (an acceleration of about 10G) and the player's world rank at present is the twelfth rank, the defense capacity D will be:

$$V = 0.8 \times 21 = 16.8 = 16$$

Thus, from the defense capacity setting table (see FIG. 6), it is found that defense capacity D = 0.

FIGS. 7A and 7B are ranking update tables referred to when the number of places up or down in world ranking according to the victory or defeat pattern in the game mode of the wristwatch device is determined-- FIG. 7A is a number-of-ranks-up setting table according to the victory pattern and FIG. 7B is a number-of-ranks-down setting table according to the defeat pattern.

Both of the rank-up table and rank-down table are stored in the ROM 19 beforehand.

In this case, the highest place in world ranking is a champion. It is assumed that the champion is not exceeded no matter how many ranks are left for the player to go up.

For example, when the player has knocked out the opponent in the second round in the fighting sport game, his rank goes up three places in world ranking. When the player has won as a result of a comparison of the number of stamina points at the end of the round, his rank goes up one place and the contents of the world rank register 20i is updated.

On the other hand, for example, when the player has been knocked out in the second round of the fighting sport game, his rank goes down three places in world ranking. When the player has been defeated as a result of a comparison of the number of stamina points at the end of the round, his rank goes down one place and the contents of the world rank register 20i is updated.

FIG. 8 is views of the initial screens corresponding to the individual operation modes of the wristwatch device. Illustration (A) in FIG. 8 is a view of the initial screen in the basic watch mode. Illustration (B) in FIG. 8 is a view of the initial screen in the power measurement mode. Illustration (C)

in FIG. 8 is a view of the initial screen in the game mode.

Each time the SM key provided in the key section 15 is operated, the operation modes of the wristwatch device are switched in this order: the basic watch mode → the power measurement mode → the game mode → the basic watch mode. As shown in illustration (A) in FIG. 8, on the initial screen in the basic watch mode, the present time appears in the lower display area of the display section 22 according to the date and time data obtained from the time and date counting circuit 18.

As shown in illustration (B) in FIG. 8, on the initial screen in the power measurement mode, each time the S3 key provided in the key section 15 is operated, the measurement numbers indicating a first, second, and third measurement modes appear in the upper display area of the display section 22 and are switched in this order: P-1, P-2, and P-3. In the lower display area, the punch destructive power (POWER) and punching speed (SPEED) measured in the preceding session in each measurement mode appear.

As shown in illustration (C) in FIG. 8, on the initial screen in the game mode, a punching game image with the stamina level of the player (left) and that of the opponent (right) appear in the upper display area of the display section 22. In the lower display area,

the player's record against the opponent and his world rank (RANK) at present appear.

Next, the power measurement operation of the wristwatch device thus constructed will be explained.

5           FIG. 9 is a flowchart of the measurement mode process in the power measurement mode of the wristwatch device.

10           FIG. 10 is a flowchart of the measurement process in the measurement process in the power measurement mode of the wristwatch device.

FIG. 11 illustrates display operations in the measurement mode process in the power measurement mode of the wristwatch device.

15           FIG. 12 is a timing chart for changes in the sound and representation in the measurement process in the power measurement mode of the wristwatch device.

20           When the SM key in the key section 15 is operated, the power measurement mode process of FIG. 9 is started. With the initial screen on which the measurement number P-1 indicating the first measurement mode appears in the upper display area of the display section 22 as shown in illustration (C1) in FIG. 11 and the punch destructive power (POWER) and punching speed (SPEED) measured in the preceding session in the first  
25           measurement mode appears in the lower display area, when the S1 key in the key section 15 is operated, the screen is changed to the maximum value recall screen as

shown in illustration (A) in FIG. 11. Then, the past maximum punch destructive power and punching speed (MAX. POWER/SPEED) stored in the maximum value register 20d of the RAM 20 are read out and forced to appear on the display section 22 for a specific period of time (step A1 → step A2).

With the initial screen in the power measurement mode as shown in illustration (C1) in FIG. 11, when the S2 key in the key section 15 is operated, the screen is changed to the player's weight and dominant arm setting screens as shown in illustrations (B1) and (B2) in FIG. 11. Depending on a combination of S1 key and S3 key, the player's weight or dominant arm are set and displayed and are stored in the weight register 20e and dominant arm register 20f in the RAM 20, respectively (step A3 → step A4).

With the initial screen in the power measurement mode as shown in illustration (C1) in FIG. 11, when the S3 key in the key section 15 is operated, each time the S3 key is operated, the measurement numbers indicating the first, second, and third measurement modes are switched and displayed in this order: P-1, P-2, and P-3 (step A5 → step A6).

Then, for example, with the first measurement mode in operation as shown in (C1) in FIG. 11, when the FO key in the key section 15 is operated, the measurement process of FIG. 10 is started (step A7 → step AB).

This changes the screen to the measurement standby screen as shown in illustration (C2) in FIG. 11, which provides sound and display as a result of a countdown of three seconds with timing T1 to T3 as shown in FIG. 12 (step B1).

Then, when a measurement start sound is produced with timing T4 in FIG. 12, the screen is changed to the in-measurement screen as shown in illustration (C3) in FIG. 11. With timing T5, the acceleration sensor 12 is set to ON to sense the acceleration as a result of the punching action of the player. Then, the A/D converted acceleration data is supplied to the CPU 13 (steps B2, B3).

Then, with timing T5 of FIG. 12, a measurement end sound is produced. Then, the punching speed V is calculated using equation 1 on the basis of the maximum punch acceleration data C sensed by the acceleration sensor 12 via the A/D conversion circuit 14 as a result of the punching of the player. At the same time, the punch destructive power (impact force) P is calculated using equation 2 on the basis of the punching speed V and the first player's weight W stored in the weight register 20e in the RAM 20. The punching speed and the punch destructive power are stored in the first measurement register 20a in the RAM 20 (step B5).

Here, the punching speed V and punch destructive power P stored in the first measurement register 20a in

the present power measurement are compared with the maximum punching speed  $V_{max}$  and maximum punch destructive power  $P_{max}$  stored in the maximum value register 20d in the RAM 20 to judge whether the former are the largest at that time (step B6).

For example, if it has been judged that the punching speed  $V$  and punch destructive power  $P$  of the first player in the present power measurement are the largest at that time, the punching speed  $V$  and punch destructive power  $P$  of the first player are stored in the maximum value register 20d in the RAM 20 as the maximum punching speed  $V_{max}$  and maximum punch destructive power  $P_{max}$ , thus updating the latter (step B6 → step B7).

Then, with timing T7 of FIG. 12, a measurement result sound is produced and simultaneously the screen is changed to the measurement result screen as shown in illustration C4 in FIG. 11, on which the punch destructive power (POWER) and punching speed (SPEED) of the first player stored in the first measurement register 20a in the RAM 20 appear (step B8).

Thereafter, when the power of a second player and that of a third player are measured, the operation of the S3 key in the key section 15 switches the measurement mode to the second measurement mode (P-2) or the third measurement mode (P-3). Then, by the same processes as described above, the punching speed  $V$  and



punch destructive power  $P$  are calculated on the basis of the punch acceleration  $C$  of each player. The calculation results are stored in the second measurement register 20b or third measurement register 20c in the RAM 20.

Therefore, in the power measurement mode process in the wristwatch device thus constructed, when the player punches with the wristwatch device on his arm, the punching speed  $V$  is determined by simple calculations on the basis of the punch acceleration  $C$  sensed by the acceleration sensor 12. At the same time, the punch destructive power (impact force)  $P$  is determined by simple calculations on the basis of the punching speed  $V$  and the player's weight  $W$ . The punching speed and punch destructive power are forced to appear on the display section 22, which enables the player to measure the speed and destructive power (impact force) corresponding to the punching action of his own body with the compact configuration.

Next, the game operation of the wristwatch device having the above-described configuration will be explained.

FIG. 13 is a flowchart for the game mode process in the punching game mode of the wristwatch device.

FIG. 14 is a flowchart for the battle process in the game mode process in the punching game mode of the wristwatch device.

FIG. 15 shows display operations in the game mode process in the punching game mode of the wristwatch device.

FIG. 16 is a timing chart to help explain the elapsed time in the game mode process in the punching game mode of the wristwatch device.

When the game mode process of FIG. 13 is started by the operation of the SM key in the key section 15, a punching game image, together with the stamina level (an initial value of 50 points) of the player (left) and the opponent (right) stored in the player's stamina register 20g and opponent stamina register 20h in the RAM 20 appears in the upper display area of the display section 22. In the lower display area, the player's record against the opponent and present world rank (RANK) stored in the number-of-wins-and-defeats register 20j and world rank register 20i in the RAM 20 appear (step C1).

With the initial screen in the game mode of illustration (A) in FIG. 15, when the S1 key in the key section 15 is operated, a "KO" image appears in the upper display area of the display section 22 for a specific period of time as shown in illustration (B1) in FIG. 15. At the same time, the number-of-past-KO-wins-and-defeats stored in the number-of-KO-wins-and-defeats register 20k in the RAM 20 is read out and displayed in the lower display area (step C2 → step

C3 → step C4).

With the initial screen in the game mode of illustration (A) in FIG. 15, when the FO key in the key section 15 is operated, the screen is changed to the standby screen as shown in illustration (C1) in FIG. 15. In the middle of the lower display area of the display section 22, the present round mark "1" appears. At the same time, with timing T1 to T2 of FIG. 16, standby sound is produced as a result of a countdown of three seconds (step C2 to step C5).

After the countdown in the game standby process has ended with timing T2 of FIG. 16, the screen is changed to the game start screen as shown in illustration (C2) in FIG. 15 and the battle process (the first round) of FIG. 14 is started (step CD).

In the battle process, with timing T2 to T3 of FIG. 16, the battle time of the first round is set to ten seconds or fifteen seconds, depending on the player's present world rank stored in the world rank register 20i in the RAM 20. During the battle time of the first round, an offensive sound indicating the attacking timing of the player's punch, a defensive sound indicating the timing of protecting the player from the attack of the opponent, and a dummy sound meaning a feint against the opponent's attack are produced with random timing.

In this case, the number of generations of the

offensive sound and defensive sound is set to three to six times, depending on the player's present world rank stored in the world rank register 20i in the RAM 20. The dummy sound is generated once or no times for the  
5 tenth world rank or higher immediately before the generation of the defensive sound.

Specifically, in the battle process of FIG. 14, for example, when an offensive sound is produced at the alarm section 21 with the timing of producing an  
10 offensive sound, the screen is changed to the attach chance screen as shown in illustration (C2a) in FIG. 15. At the same time, the acceleration sensor 12 is set to ON and senses the acceleration caused by the offensive punching action of the player. Then, the A/D converted  
15 acceleration data is supplied to the CPU 13 (step D1 → step D2 and step D3).

Then, the punching speed  $V$  is calculated using equation 1 on the basis of the maximum punch acceleration data  $C$  caused by the defensive punching action of  
20 the player sensed by the acceleration sensor 12 via the A/D conversion circuit 14. At the same time, the offensive strength  $A$  is calculated using equation 3, on the basis of the punching speed  $V$  and the coefficient  $K$  corresponding to the player's present world rank  
25 obtained from the data in the table (see FIG. 5) stored in the ROM 19. Then, the offensive strength  $A$  is subtracted from the opponent's stamina points stored in

the opponent stamina register 20h in the RAM 20 (step D4 and step D5).

Here, it is judged whether or not the opponent's stamina points have reached "0." If it has been judged that they have not reached "0," control will be returned to the state where the timing of producing an offensive sound and a defensive sound is waited for. If it has been judged that they have reached "0," the process of displaying "KO WIN" on the display section 22 will be carried out and thereafter control will be passed to step C11 of FIG. 13, where the win or defeat display process will be executed (step D6 → step D7 → KO).

Furthermore, when the timing of generating a defensive sound has been reached, it is judged whether or not the generation of a dummy sound is necessary (step D8 → step D9). When the timing of generating a dummy sound has been reached, the alarm section 21 generates a dummy sound (step D9 → step D10) and 0.5 seconds later, a defensive sound is generated (step D11 → step D12).

The, as shown in illustration (C2b) in FIG. 15, the screen is changed to the defense screen. At the same time, the acceleration sensor 12 is set to ON to sense the acceleration caused by the player's defending action. Then, the A/D converted acceleration data is supplied to the CPU 13 (step D13).

Then, the defense speed  $V$  is calculated using equation 1 on the basis of the acceleration data  $C$  concerning the player's defending action sensed by the acceleration sensor 12 via the A/D conversion circuit 14. Thereafter, on the basis of the defense speed  $V$  and the table data (see FIG. 6) stored in the ROM 19, the defense capacity (the player's damage)  $D$  according to the player's present world rank is determined. Then, the defense capacity  $D$  is subtracted from the player's stamina points stored in the player's stamina register 20g in the RAM 20 (steps D14, D15).

Then, it is judged whether or not the player's stamina points have reduced to zero. If it has been judged that they have not reduced to zero, control will be returned to the state where the timing of generating an offensive sound and defensive sound is waited for. If it has been judged that they have reduced to zero, "KO DEFEAT" will be forced to appear on the display section 22 and thereafter control will be passed to the victory or defeat display process of step C11 in FIG. 13 (step D16  $\rightarrow$  step D17  $\rightarrow$  KO).

In the state where neither the player's stamina points stored in the player's stamina register 20g in the RAM 20 nor the opponent's stamina points stored in the opponent stamina register 20h are "0," when it has been judged that a specific period of time has elapsed with timing  $T3$  of FIG. 16, the battle process in the

first round is terminated (step D18 → END).

Then, with timing T4 of FIG. 16, control proceeds to the result display process in the first round as shown in illustration (C3) in FIG. 15, the player's remaining stamina points stored in the player's stamina register 20g in the RAM 20 and the opponent's remaining stamina points stored in the opponent stamina register 20h are displayed in level form (step C6) on the left and right scales.

After the game standby process, battle process, and result display process concerning the first round of the punching game have been completed through steps C5, CD (D1 to D18), and C6, the game standby process concerning the second round is started, followed by the battle process and the result display process, as described above (steps C7, CD, C8).

After the game standby process, battle process, and result display process concerning the second round have been completed, the game standby process concerning the third round is started, followed by the battle process and the result display process, as described above (steps C9, CD, C10).

Then, when the first to third rounds of the punching game have ended or when either the opponent's stamina points or the player's stamina points have reduced to zero and the result is a KO win or a KO defeat in one of the first to third rounds, the screen

on the display section 22 is changed to the victory or defeat screen as shown in illustration (D) in FIG. 15, where the player's remaining stamina points stored in the player's stamina register 20g in the RAM 20 and the opponent's remaining stamina points stored in the opponent stamina register 20h are displayed in level form on the left-side and right-side scales in the upper display area. At the same time, in the lower display area, the player's and opponent's stamina points are displayed in numeric form and a winner image determined by the comparison of the remaining stamina points is displayed in the upper middle image display area (step C11).

Then, the number of wins and defeats stored in the number-of-wins-and-defeats register 20j in the RAM 20 is updated. Moreover, in the case of a KO win or defeat, the number of KO wins and defeats stored in the number-of-KO-wins-and-defeats register 20k is also updated.

Depending on whether the win or defeat result obtained in the win or defeat display process comes from a decision on remaining points or from a KO in one of the first to third round battle processes, the player's present world rank stored in the world rank register 20i in the RAM 20 goes up or down, thereby updating the player's rank (step C12).

Then, as shown in illustration (E) in FIG. 15, in



the lower display area of the display section 22, the number of wins and defeats of the player after the game updated in the number-of-wins-and-defeats register in the RAM 20 and the player's world rank updated in the world rank register 20i appear (step C13).

With the game mode process in the wristwatch device having the aforementioned configuration, when the player punches and defends with the wristwatch device on his arm in response to an offensive sound and defensive sound produced at random at the alarm section 21, the offensive strength A is calculated during the punching action on the basis of the acceleration data sensed by the acceleration sensor 12 and the opponent's stamina points stored in the opponent stamina register 20h are reduced. During the defending action, the defense capacity (the player's damage) D is calculated and the player's stamina points stored in the player's stamina register 20g are reduced. The win or defeat result is displayed, depending on the amount of the player's and opponent's remaining stamina points, which enables the player to easily play a fighting sport game involving the actual punching action of the player anywhere.

## (2) Second Embodiment

Hereinafter, a second embodiment of the present invention will be explained by reference to FIGS. 17 and 18. The same parts as those in the first

embodiment will be indicated by the same reference symbols and explanation of them will not be given.

FIG. 17 is a block diagram of the circuit of an electronic wristwatch according to a second embodiment of the present invention. The block diagram of FIG. 17 differs from that of FIG. 3 in that the former includes a transceiver section 31.

The transceiver section 31 transmits and receives data by infrared rays or by radio. It exchanges offensive strength data during an attack and defense capacity during defense with the opponent's game machine.

Next, the contents of the game process in the second embodiment will be described by reference to the flowchart of FIG. 18.

At step S1 in FIG. 18, which of the two game machines attacks first is determined at random. At step S2, it is judged whether or not one player's game machine is allowed to attack first. If the player is allowed to attack first, an offensive sound will be produced at step S3 and then the acceleration will be sensed by the acceleration sensor 12 for ten seconds. The reason why the acceleration is sensed for ten seconds since the generation of the offensive sound is that the opponent player is allowed to determine offensive timing arbitrarily within the ten seconds.

At step S5, the offensive strength is sensed, that

is, the maximum value of the acceleration sensed by the acceleration sensor 12 during ten seconds is found. Then, the offensive strength calculated at step S6 is sent to the transceiver section 31, which transmits it to the opponent game machine. At the following step S7, it is judged whether or not the defense capacity of the opponent has been received. Here, the defense capacity is the maximum value of the acceleration caused by the action of drawing in the arm. Because the direction of the acceleration caused by the action of drawing in the arm during defense is the opposite of the direction of the action of striking straight ahead during an attack, the damage that the player or the opponent has suffered as a result of an attack is calculated by subtracting the defense capacity from the offensive strength. The process at step S7 is repeated until the player's game machine has received the defense capacity of the opponent. If the player's game machine has received the defense capacity, it will calculate damage from the player's offensive strength and the defense capacity of the opponent.

In this fighting sport game, specific stamina points are given to each player at the start of the game. The damage that each player has suffered from the opponent is subtracted from his stamina points. Each player is allowed to attack and defend five times. The player whose stamina points are fewer than those of

the opponent or the player whose stamina points have reduced to zero in the course of the game loses.

At step S9, the damage that the opponent has suffered is calculated from the player's offensive strength and the opponent's defense capacity. The  
5 calculated damage is subtracted from the stamina points that the opponent has at present, thereby updating the opponent's stamina points.

The opponent's stamina points and the player's  
10 stamina points are stored in the registers in the RAM 20. At step S9, the opponent's and player's stamina points are updated.

Then, at step S10, it is judged which player has no stamina points left. If both players have stamina  
15 points left, or the number of stamina points of both players is not zero, control will proceed to step S11, where it will be judged whether or not each of attacking and defending has been done five times. When both of attacking and defending have been done five  
20 times, or when at step S10, it has been judged that the number of stamina points is zero, the player's stamina points are compared with the opponent's stamina points and the one who has more stamina points is determined to be a winner.

25 When at step S11, each of attacking and defending has not been done five times, or when at step S2, it has been judged that the player is not allowed to

attack first, control will proceed to step S13, where the player's machine has received the offensive strength from the opponent's machine. If it has not received the offensive strength, the process at step

5 S13 is repeated until the transceiver section 31 has received the opponent's offensive strength. If the transceiver section 31 has received the opponent's offensive strength, a defense sound that informs the player that he has been attacked will be generated at

10 step S14. At step S15, the acceleration sensor 12 is turned on for 1.8 seconds to sense the maximum value of the acceleration of the offensive strength. The reason why the time during which the acceleration sensor 12 remains on is limited to 1.8 seconds is to limit the

15 response time from the instance that the player was attached to when he starts to defend. That is, when the player defends rapidly within 1.8 seconds since he heard the defense sound, the defensive strength is effective, but when he reacts later than 1.8 seconds,

20 the defensive strength is invalid.

When the player's machine has obtained the defense capacity, it causes the transceiver section 31 to transmit the defense capacity to the opponent. At step

S18, the damage that the player has suffered from the

25 attack is calculated by subtracting the player's defense capacity from the opponent's offensive strength received by the transceiver section 31. At step S19,

the damage is subtracted from the player's stamina points, thereby updating his stamina points. At the same time, the opponent damage is subtracted from the opponent's stamina points, thereby updating the opponent's stamina points. Then, at step S20, it is judged which player has no stamina points left. If the number of stamina points is not zero, it will be judged whether or not each of attacking and defending has been done five times. If both of attacking and defending have been done five times, victory or defeat will be determined from the player's and opponent's stamina points at step S12. The result is forced to appear on the display section 22. If attacking and defending have not been done five times, control will return to step S3, where the processes for attacking and defending will be repeated.

While in the second embodiment, the attacking side receives the opponent's defense capacity and calculates the opponent's damage from the opponent's defense capacity and the attacking side's offensive strength, the opponent side may calculate its own damage and the remaining stamina points and transmit the calculated stamina points to the attacking side.

While in the embodiments, the case where the present invention has been applied to the fighting sport game has been explained, the invention may be applied to various games.

For instance, the present invention may be applied to a baseball game (pitching game) and a dodge ball game by sensing the speed at which the player throws a ball with a movement measuring device. The invention  
5 may be also applied to a tennis game, a golf game, and a baseball game (batting game) by sensing the strength of swing with a movement measuring device.

While in the embodiments, the movement measuring device is worn on the arm, it may be worn on the ankle  
10 and the strength of a kick be measured. In this case, the present invention may be applied to a soccer game in addition to fighting sport games.

## C L A I M S

1. A movement measuring device comprising:  
acceleration sensing means that is worn on the  
body and senses the acceleration of the body's  
5 movement;

maximum acceleration sensing means for sensing  
the maximum value of the acceleration sensed by said  
acceleration sensing means in the course of a specific  
movement of the body; and

10 speed computing means for determining the speed  
produced by the specific movement of the body on the  
basis of the maximum value of the acceleration sensed  
by said maximum acceleration sensing means.

2. A movement measuring device according to  
15 claim 1, further comprising:

weight input means for inputting weight; and

impact force computing means for determining the  
impact force caused by the specific movement of said  
body on the basis of the weight inputted from said

20 weight input means and the speed obtained at said speed  
computing means.

3. A movement measuring device according to  
claim 1, wherein said speed computing means determines  
the speed by multiplying said maximum acceleration by a  
25 constant.

4. A movement measuring device according to  
claim 2, wherein said impact force computing means



determines the impact force by multiplying the square of the speed obtained at said speed computing means by the weight inputted from said weight input means and a constant.

5           5. A movement measuring device according to claim 1, further comprising display means for displaying the speed obtained at said speed computing means.

10           6. A movement measuring device according to claim 2, further comprising display means for displaying the impact force obtained at said impact force computing means.

15           7. A movement measuring device according to claim 1, wherein the device is housed in a case having bands at both ends that enable the device to be worn on the body.

20           8. A movement measuring device according to claim 7, wherein said acceleration sensing means senses the acceleration in the direction perpendicular to the direction in which said bands are worn.

          9. A movement measuring device according to claim 1, wherein the device is housed in a case having bands at both ends that enable the device to be worn on the arm.

25           10. A movement measuring device according to claim 9, wherein said acceleration sensing means senses the acceleration in the direction from three o'clock to

nine o'clock or vice versa on the face of a watch.

11. A movement measuring device according to claim 9, further comprising time display means for displaying the time on said case.

5 12. An electronic game machine comprising:  
acceleration sensing means that is worn on the body and senses the acceleration of the body's movement;

10 computing means for obtaining data indicating the magnitude of movement on the basis of the acceleration sensed by said acceleration sensing means; and

15 decision means for determining victory or defeat on the basis of the data indicating the magnitude of a specific movement of the body obtained by said computing means.

13. An electronic game machine according to claim 12, wherein said computing means includes means for obtaining the data based on the acceleration sensed during a first period, and means for obtaining the data based on the acceleration sensed during a second period,  
20 and

said decision means determines victory or defeat on the basis of the data based on the acceleration sensed during said first period and the data based on the acceleration sensed during said second period.  
25

14. An electronic game machine according to claim 12, further comprising sound generation means for

producing different sounds corresponding to said first period and said second period.

15        15. An electronic game machine according to claim 12, further comprising display means for displaying the victory or defeat determined by said decision means.

10        16. An electronic game machine according to claim 12, wherein the machine is housed in a case having bands at both ends that enable the machine to be worn on the body.

17. An electronic game machine according to claim 16, wherein said acceleration sensing means senses the acceleration in the direction perpendicular to the direction in which said bands are worn.

15        18. An electronic game machine according to claim 12, wherein the machine is housed in a case having bands at both ends that enable the device to be worn on the arm.

20        19. An electronic game machine according to claim 18, wherein said acceleration sensing means senses the acceleration in the direction from three o'clock to nine o'clock or vice versa on the face of a watch.

25        20. A movement measuring device according to claim 18, further comprising time display means for displaying the time on said case.

21. An electronic game machine according to

claim 12, further comprising receiving means for receiving the data transmitted from an external device, wherein

5       said decision means determines victory or defeat on the basis of the data obtained at said computing means and the data received by said receiving means.

22. An electronic game machine according to claim 21, further comprising transmission means for transmitting the data obtained at said computing means.

10       23. A method of measuring the magnitude of a specific movement, comprising the steps of:

      sensing the maximum value of the acceleration of a specific movement on the basis of the acceleration obtained at acceleration sensing means worn on the  
15       body; and

      determining the speed of said specific movement on the basis of the maximum value of the acceleration.

24. A method according to claim 23, further comprising the steps of:

20       inputting weight; and

      determining the impact force caused by the specific movement of said body on the basis of the weight inputted in said weight inputting step and the speed obtained in the movement speed determining step.

25       25. A method according to claim 23, wherein said speed determining step determines the speed by multiplying said maximum acceleration by a constant.

26. A method according to claim 24, wherein said impact determining step determines the impact force by multiplying the square of the speed obtained in said speed determining step by the weight inputted in said weight inputting step and a constant.

27. A method according to claim 23, further comprising the step of displaying the speed obtained in said speed determining step.

28. A method according to claim 24, further comprising the step of displaying the impact force obtained in said impact force determining step.

29. An electronic game method comprising the steps of:

sensing the acceleration produced by a specific movement by means of acceleration sensing means worn on the body;

obtaining the data indicating the magnitude of the movement from acceleration; and

determining victory or defeat on the basis of the data indicating the magnitude of the movement.

30. An electronic game method according to claim 29, wherein said step of obtaining the data indicating the magnitude of the movement includes the step of obtaining the data based on the acceleration sensed during a first period, and the step of obtaining the data based on the acceleration sensed during a second period, and

said step of determining victory or defeat includes the step of determining victory or defeat on the basis of the data based on the acceleration sensed during said first period and the data based on the acceleration sensed during said second period.

31. An electronic game method according to claim 29, wherein said step of determining victory or defeat includes the steps of:

changing a player's points and the opponent's points on the basis said acceleration; and

determining victory or defeat by comparing the player's points with the opponent's points.

32. An electronic game method according to claim 29, further comprising the step of displaying victory or defeat.

33. An electronic game method according to claim 29, further comprising the step of receiving the data transmitted from an external device, wherein

said victory or defeat determining step determines victory or defeat on the basis of the data received in the receiving step and the data obtained in said step of obtaining the data indicating the movement.

34. An electronic game method according to claim 33, further comprising the step of transmitting the data obtained in the step of obtaining the data indicating the magnitude of said movement.

35. A program storage medium having

computer-readable program codes for measuring the magnitude of a specific movement, comprising:

computer-readable program code means for sensing the maximum value of the acceleration of a specific movement on the basis of the acceleration obtained from acceleration sensing means worn on the body; and

computer-readable program code means for obtaining the speed of said specific movement from the maximum value of the acceleration.

36. A program storage medium according to claim 35, further comprising:

computer-readable program code means for inputting weight; and

computer-readable program code means for calculating the impact force caused by said specific movement of the body on the basis of the inputted weight and said speed of the movement.

37. A program storage medium according to claim 35, further comprising computer-readable program code means for displaying the speed of said movement.

38. A program storage medium according to claim 35, further comprising computer-readable program code means for displaying said impact force.

39. A program storage medium having computer-readable program codes for executing a game using the acceleration sensed by acceleration sensing means worn on the body, comprising:

computer-readable program code means for, when the body makes a specific movement, obtaining data indicating the magnitude of said specific movement on the basis of the acceleration sensed by said acceleration sensing means; and

computer-readable program code means for determining victory or defeat on the basis of the data indicating the magnitude of said movement.

40. A program storage medium according to claim 39, further comprising:

computer-readable program code means for obtaining the data based on the acceleration sensed by said acceleration sensing means during a first period;

computer-readable program code means for obtaining the data based on the acceleration sensed by said acceleration sensing means during a second period; and

computer-readable program code means for determining victory or defeat on the basis of the data based on the acceleration sensed during the first period and the data based on the acceleration sensed during the second period.

41. A program storage medium according to claim 39, further comprising:

computer-readable program code means for changing a player's points and the opponent's points on the basis of the data indicating the magnitude of the movement; and



computer-readable program code means for determining victory or defeat by comparing the player's points with the opponent's points.

42. A program storage medium according to claim 39,  
5 further comprising computer-readable program code means for displaying victory or defeat.

43. A program storage medium according to claim 39, further comprising:


10 computer-readable program code means for receiving the data transmitted from an external device; and

computer-readable program code means for determining victory or defeat on the basis of the received data and the data obtained by said program code means for obtaining data indicating said movement.


15 44. A program storage medium according to claim 43, further comprising computer-readable program code means for transmitting the data indicating the magnitude of said movement.

1/16

**FIG.1A**




**FIG.1B**



2/16

FIG.2



3/16

FIG.3




FIG.4

20 RAM

20a	FIRST MEASUREMENT SPEED/DESTRUCTIVE POWER		PLAYER'S OWN STAMINA	20g
20b	SECOND MEASUREMENT		OPPONENT'S STAMINA	20h
20c	THIRD MEASUREMENT		WORLD RANK	20i
20d	MAXIMUM VALUE SPEED/DESTRUCTIVE POWER		NO. OF WINS AND DEFEATS	20j
20e	WEIGHT	DOMINANT ARM	NO. OF KO WINS AND DEFEATS	20k
20f				

4/16

FIG.5

WORLD RANKING	K VALUE
CHAMP TO 10TH RANK	0.006
11TH TO 20TH RANKS	0.007
21TH TO 30TH RANKS	0.020

NOTE: K IS A COEFFICIENT INCLUDING WORLD RANK AND SPECIFIC WEIGHT

FIG.6

DEFENCE SPEED \ WORLD RANK	CHAMP TO 10TH RANK	11TH TO 20TH RANKS	21TH TO 30TH RANKS
12 OR MORE	-5	0	0
6~11	-10	-5	-5
0~5	-20	-15	-10

FIG.7B

< DEFEAT RANK POINTS >

DEFEAT PATTERN	RANKS UP
1ST ROUND KO	-5
2ND ROUND KO	-3
3RD ROUND KO	-2
REMAINING STAMINA JUDGMENT	-1


FIG.7A

< VICTORY RANK POINTS >

VICTORY PATTERN	RANKS UP
1ST ROUND KO	+5
2ND ROUND KO	+3
3RD ROUND KO	+2
REMAINING STAMINA JUDGMENT	+1


6/16

FIG.8




7/16

FIG. 9






8/16

**FIG.10**


9/16

FIG.11




10/16

FIG.12




11/16

FIG.13



12/16

FIG.14



13/16

FIG.15






FIG.16



15/16


FIG.17





16/16

FIG.18








## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification 6 :</b> <b>G01P 15/08, 15/04, 7/00, A63F 9/22, G06F 3/00</b>	<b>A3</b>	<b>(11) International Publication Number:</b> <b>WO 97/46888</b> <b>(43) International Publication Date:</b> 11 December 1997 (11.12.97)
<b>(21) International Application Number:</b> PCT/JP97/01730 <b>(22) International Filing Date:</b> 23 May 1997 (23.05.97) <b>(30) Priority Data:</b> 8/143028      5 June 1996 (05.06.96)      JP <b>(71) Applicant (for all designated States except US):</b> CASIO COMPUTER CO., LTD. [JP/JP]; 6-1, Nishi-Shinjuku 2-chome, Shinjuku-ku, Tokyo 160 (JP). <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> TONOMURA, Keisuke [JP/JP]; 1-22-37-103, Musashinodai, Fussa-shi, Tokyo 197 (JP). YAMAGISHI, Masakatsu [JP/JP]; 1202, Fussa, Fussa-shi, Tokyo 197 (JP). <b>(74) Agents:</b> SUZUYE, Takehiko et al.; Suzuye & Suzuye, 7-2, Kasumigaseki 3-chome, Chiyoda-ku, Tokyo 100 (JP).		<b>(81) Designated States:</b> CN, KR, SG, US, European patent (DE, FR, GB, IT). <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> <b>(88) Date of publication of the international search report:</b> 29 January 1998 (29.01.98)

**(54) Title:** MOVEMENT MEASURING DEVICE, ELECTRONIC GAME MACHINE INCLUDING MOVEMENT MEASURING DEVICE, AND METHOD OF PLAYING GAME MACHINE

**(57) Abstract**

A movement measuring device determines the speed of the body's specific movement on the basis of the maximum value of the acceleration sensed by an acceleration sensing unit attached to the body, when the body has made a specific movement. For example, when the player wears the device on his arm and makes a punching motion, the punching speed is found from the maximum acceleration resulting from the punching action. Furthermore, a game device obtains data indicating the magnitude of a specific movement of the body, on the basis of the acceleration sensed by an acceleration sensing unit, and then decides the outcome of the game is decided on the basis of the strength and weakness of the punch. This enables the user to easily play a fighting sport game involving the player's actual punching motions anywhere.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

# INTERNATIONAL SEARCH REPORT

Internat'l Application No  
PCT/JP 97/01730

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G01P15/08 G01P15/04 G01P7/00 A63F9/22 G06F3/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G01P G06K A63B A63F G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 967 596 A (RILLING JOHN F ET AL) 6 November 1990	1,23
A	see column 5, line 2 - line 32; figure 4	35
A	DE 38 42 434 A (GERLACH THOMAS K) 7 December 1989	1,7,9, 23,35
	see page 2, line 32 - page 3, line 65	
A	GB 2 194 338 A (WONG T K ASS LTD) 2 March 1988	1,23,35
	see page 1, line 10 - line 18	
A	WO 91 06348 A (BATRONICS INC) 16 May 1991	1,2,5,6
	see page 9, last paragraph	
	see page 14, line 4 - line 24	
	see page 16, paragraph 3 - page 18, paragraph 1; figures 8,12A-D,14	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

\*Z\* document member of the same patent family

Date of the actual completion of the international search

14 November 1997

Date of mailing of the international search report

- 2. 12. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Pflugfelder, G

# INTERNATIONAL SEARCH REPORT

Internat. Application No.  
PCT/JP 97/01730

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 229 756 A (KOSUGI NAOHIRO ET AL) 20 July 1993  see column 3, line 58 - column 5, line 68 see column 7, line 37 - column 11, line 10 see column 15, line 34 - column 17, line 34; figures ---	12-19, 21,22, 29-34, 39-44
Y	US 5 516 105 A (EISENBREY GLEN T ET AL) 14 May 1996  see the whole document ---	12-16, 18,21, 22, 29-34, 39-44
A	US 4 699 379 A (CHATEAU ROBERT E ET AL) 13 October 1987 ---	7,9
Y	see column 3, line 1 - column 4, line 49; figures 1,2  ---	12,14, 16-19, 29,30,39
A	US 5 354 057 A (PRUITT RALPH T ET AL) 11 October 1994  see column 6, line 30 - column 10, line 36; figures -----	12-16, 21,22, 29-34, 39-44

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP 97/ 01730

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see continuation sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest
- ☒ No protest accompanied the payment of additional search fees.

# INTERNATIONAL SEARCH REPORT

International Application No. PCT/ JP 97/01730

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

1. claims 1-11,23-28,35-38:

Movement measuring device with speed computing on the basis of sensed maximum value of acceleration.

2. claims 12-22,29-34,39-44

Electronic game machine with computing means for magnitude of movement on the basis of sensed acceleration and victory/defeat judgement on basis of magnitude of movement



# INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern: al Application No  
PCT/JP 97/01730

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4967596 A	06-11-90	NONE	
DE 3842434 A	07-12-89	NONE	
GB 2194338 A	02-03-88	NONE	
WO 9106348 A	16-05-91	US 5056783 A CA 2027853 A	15-10-91 19-04-91
US 5229756 A	20-07-93	JP 2209169 A	20-08-90
US 5516105 A	14-05-96	NONE	
US 4699379 A	13-10-87	NONE	
US 5354057 A	11-10-94	NONE	

**THIS PAGE BLANK (USPTO)**